

MATERIAL SAFETY DATA SHEET

Manufacturer: OMNI/ajax
Address: 49 Pocono Forest
Gouldsboro, PA 18424
Phone (570)-848-4186

Product Name: OMNI-FIX™
MSDS #: N/A
CAS#: See below
Date Prepared: 6.10.08
Prepared by: MAC

MATERIAL IDENTIFICATION and INFORMATION:

Portland Cement CAS# 6599-71-51; Magnesium Silicofluoride CAS# 16949-65-8; Kaolin CAS# 1332-58-7; Activated Charcoal CAS# 7440-44-0; TriSodium Phosphate CAS# 10101-89-0

PHYSICAL and CHEMICAL CHARACTERISTICS:

Boiling Point: N/A
Vapor Pressure: N/A
Solubility in Water: Insoluble
Appearance and Odor: Grey dry powder 20 mesh-300 mesh.

Specific Gravity: 0.49 30#/cu. ft
Evaporation Rate: N/A
Water Reactive: Non reactive

FIRE and EXPLOSION HAZARD:

Flash Point: N/A
Auto-Ignition Temperature: N/A
Unusual Fire and Explosion Hazards: None
Special Fire Fighting Procedure: None

Extinguisher Medium: Water
Flammability Limits in Air: N/A

REACTIVITY HAZARD DATA:

Stable; Conditions to Avoid: Contact with strong acids. Hazardous Decomposition Products: None.

HEALTH HAZARD DATA:

Primary Route: Inhalation, skin contact. Ingestion. Health Hazards: Irritation of eyes, skin, and mucous membranes. Stomach Upset. Chronic: None
Eye Contact: Flush with water. Skin Contact: Flush with water. Ingestion: Take citrus juices. Inhalation: Remove to fresh air.

CONTROL and PROTECTIVE MEASURES:

Use NIOSH respirator. Goggles and gloves. Other protective clothing as required in HazMat use. Wash hands after using.

SAFE HANDLING and LEAK PROCEDURES:

Spills: Sweep up. Waste disposal methods: Sanitary landfill for unused OMNI media. Keep dry and store in a cool place.

NFPA Rating: Health 1, Flammability 0, Reactivity 1