

MATERIAL SAFETY DATA SHEET

Manufacturer: OMNI/ajax
Address: 49 Pocono Forest
Gouldsboro, PA 18424
Phone (570)-848-4186
FAX# (570)-848-4187

Product Name: SorbaSet S™
MSDS #: N/A
CAS#: See below
Date Prepared: 6.10.08
Prepared by: MAC

MATERIAL IDENTIFICATION and INFORMATION:

Gypsum CAS# 7778-18-9; Portland Cement CAS# 6599-71-51; Hydrated Lime CAS# 12001-27-3;
Mg Silicoflouride CAS # 1649-65-8; Vermiculite CAS# 1318-00-9

PHYSICAL and CHEMICAL CHARACTERISTICS:

Boiling Point: N/A
Vapor Pressure: N/A
Solubility in Water: Insoluble
Appearance and Odor: Lt. Grey dry powder 20-300 mesh
Specific Gravity: 0.6 30 lb./ cu ft.
Evaporation Rate: N/A
Water Reactive: Very slight heating

FIRE and EXPLOSION HAZARD:

Flash Point: N/A
Auto-Ignition Temperature: N/A
Unusual Fire and Explosion Hazards: None
Special Fire Fighting Procedure: None
Extinguisher Medium: Water
Flammability Limits in Air: N/A

REACTIVITY HAZARD DATA:

Stable; Conditions to Avoid: Contact with strong acids; Hazardous decomposition products: None

HEALTH HAZARD DATA:

Primary Route: Inhalation, Skin Contact. Health Hazards: Irritation of eyes, skin, and mucous membranes. Stomach upset. Chronic: None
Eye Contact: Flush with water. Skin Contact: Flush with water. Ingestion: Take citrus juices.
Inhalation: Remove to fresh air.

CONTROL and PROTECTIVE MEASURES:

Use NIOSH respirator. Goggles and gloves. Other protective clothing as required in HazMat use. Wash hands after using.

SAFE HANDLING and LEAK PROCEDURES:

Spills: Sweep up. Waste Disposal: Sanitary landfill for unused SorbaSet material. Keep dry.

NFPA Rating: Health 1, Flammability 0, Reactivity 1